

NTH

CHEMICAL PETROCHEMICAL

Oil and petroleum/Tank truck suction and discharge



Applications

Suction and discharge of petroleum products with aromatic content up to 50 % in all industrial applications.
Road tanker equipment for oil and petrol deliveries.

Advantages

- Easily cut to length and fitted with couplings.
- Light weight and flexible.
- Range of diameters enabling all couplings to be fitted either by crimping or with half shell clamps.
- Dissipation of static electricity ensured by hose tube.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.
Reinforcement: synthetic textile, braids with embedded steel helix.
Cover: oil and weather resistant NBR/PVC, black, fabric impression.
Temperature range: - 30 °C to + 80 °C .
Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.
Standard/Approval: EN 1761 type SD.

NTH

20/03/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	bar	bar	bar	mm	kg/m	m		m
19.0	6.0 ± 0.5	31.0 ± 1.0	10	40	0.9	125	0.70	20	5501515	400
								40	5501516	400
25.0	6.0 ± 0.5	37.0 ± 1.0	10	40	0.9	150	0.82	20	5501501	■
								40	5501502	■
32.0	6.0 ± 0.5	44.0 ± 1.0	10	40	0.9	175	1.07	20	5501503	■
								40	5501504	■
38.0	6.5 ± 0.6	51.0 ± 1.0	10	40	0.9	225	1.28	20	5501505	■
								40	5501506	■
50.0	8.0 ± 0.6	66.0 ± 1.2	10	40	0.9	275	2.12	20	5501507	■
								40	5501508	■
63.0	8.0 ± 0.6	79.0 ± 1.2	10	40	0.9	300	2.62	20	5501509	■
								40	5501510	■
75.0	8.0 ± 0.6	91.0 ± 1.2	10	40	0.9	350	3.28	20	5501511	■
								40	5501512	■
100.0	8.0 ± 0.6	116.0 ± 1.2	10	40	0.9	450	4.12	20	5501513	■
								40	5501514	■

Branding



and embossed: TRELLEBORG - NTH - EN 1761:1999 - SD - ND - WP 10 bar - Ω - month/year - batch number

