

# TRELLOIL D

## CHEMICAL PETROCHEMICAL

Oil and petroleum/Tank truck discharge



### Applications

Multipurpose hose especially designed for petrol, oil and other petrochemical products (with aromatic content up to 50 %).

### Advantages

- Flexible hose with very good resistance to petroleum products and weather conditions.
- Good cold flexibility.
- Dissipation of static electricity ensured by contact of built-in wire with the coupling.
- Large range of dimensions.

### Technical description

**Inner tube:** oil and petrol resistant NBR, black, smooth.

**Reinforcement:** synthetic textile.

**Cover:** oil and weather resistant SBR/NBR, black, fabric impression.

**Temperature range:** - 30 °C to + 80 °C.

**Electrical properties:** built-in conductive wire.

## TRELLOIL D

20/03/2007

| ID    | Wall thickness |       | OD    |       | Working pressure | Bursting pressure | Bending radius | Weight | Length | Article number | Stock (■) or min. order |
|-------|----------------|-------|-------|-------|------------------|-------------------|----------------|--------|--------|----------------|-------------------------|
|       | mm             | mm    | mm    | mm    |                  |                   |                |        |        |                |                         |
| 30.0  | 5.5            | ± 0.5 | 41.0  | ± 1.0 | 10               | 40                | 240            | 0.84   | 20     | 0126039        |                         |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126049        | ■                       |
| 32.0  | 5.5            | ± 0.5 | 43.0  | ± 1.0 | 10               | 40                | 250            | 0.89   | 20     | 0126051        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126052        | ■                       |
| 35.0  | 5.5            | ± 0.5 | 46.0  | ± 1.0 | 10               | 40                | 280            | 0.95   | 20     | 0126054        | 400                     |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126055        | ■                       |
| 38.0  | 6.0            | ± 0.7 | 50.0  | ± 1.0 | 10               | 40                | 300            | 1.08   | 20     | 0126062        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126066        | ■                       |
| 40.0  | 7.0            | ± 0.7 | 54.0  | ± 1.0 | 10               | 40                | 320            | 1.35   | 20     | 0126067        | 400                     |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126068        | ■                       |
| 45.0  | 7.0            | ± 0.7 | 59.0  | ± 1.0 | 10               | 40                | 360            | 1.49   | 20     | 0126069        | 400                     |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126070        | ■                       |
| 50.0  | 7.0            | ± 0.7 | 64.0  | ± 1.0 | 10               | 40                | 400            | 1.61   | 20     | 0126072        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126075        | ■                       |
| 60.0  | 7.0            | ± 0.8 | 74.0  | ± 1.5 | 10               | 40                | 480            | 2.06   | 20     | 0126086        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126087        | ■                       |
| 63.0  | 7.0            | ± 0.8 | 77.0  | ± 1.5 | 10               | 40                | 500            | 2.15   | 20     | 0126092        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126093        | ■                       |
| 70.0  | 7.5            | ± 0.8 | 85.0  | ± 1.5 | 10               | 40                | 560            | 2.58   | 20     | 0126096        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126097        | 200                     |
| 75.0  | 7.5            | ± 0.8 | 90.0  | ± 1.5 | 10               | 40                | 600            | 2.75   | 20     | 0126100        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126104        | ■                       |
| 80.0  | 7.5            | ± 1.0 | 95.0  | ± 1.5 | 10               | 40                | 640            | 2.85   | 20     | 0126105        | 200                     |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126106        | 200                     |
| 85.0  | 7.5            | ± 1.0 | 100.0 | ± 1.5 | 10               | 40                | 680            | 3.10   | 20     | 0126129        | 200                     |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126130        | 200                     |
| 89.0  | 8.0            | ± 1.0 | 105.0 | ± 1.5 | 10               | 40                | 710            | 3.40   | 20     | 0126107        | 200                     |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126108        | 200                     |
| 100.0 | 7.5            | ± 1.0 | 115.0 | ± 1.5 | 10               | 40                | 800            | 3.50   | 20     | 0126122        | ■                       |
|       |                |       |       |       |                  |                   |                |        | 40     | 0126125        | ■                       |

### Branding

