

PUMPADUKT D

CHEMICAL PETROCHEMICAL

Oil and petroleum/Tank truck discharge



Applications

Discharge of petroleum products, especially designed for applications on reels.
Road tanker equipment for oil delivery (aromatic content up to 50 %).

Advantages

- Hose can be cut to length as required.
- Cover especially designed for oil, abrasion and weather resistance.
- Electrical conductivity ensured by the tube compound.
- In compliance with chemicals industry requirements.

Technical description

Inner tube: oil and petrol resistant NBR, black, smooth.
Reinforcement: synthetic textile.
Cover: oil and weather resistant CR, black, fabric impression.
Temperature range: - 40 °C to + 100 °C .
Electrical properties: conductive tube, $R < 10^6 \Omega/\text{lg}$.
Standard/Approval: EN 1761, EN 12115.

PUMPADUKT D

19/03/2007

ID	Wall thickness	OD	Working pressure	Bursting pressure	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	bar	bar	mm	kg/m	m		m
19.0	6.0 ± 0.5	31.0 ± 1.0	16	64	125	0.65	20	0070687	400
							40	0070688	400
25.0	6.0 ± 0.5	37.0 ± 1.0	16	64	150	0.78	20	0070689	400
							40	0095761	400
32.0	6.0 ± 0.5	44.0 ± 1.0	16	64	175	0.92	20	0060106	■
							40	0126172	■
38.0	6.5 ± 0.5	51.0 ± 1.0	16	64	225	1.20	20	0123031	■
							40	0125722	■
40.0	7.0 ± 0.6	54.0 ± 1.0	16	64	240	1.35	20	0070690	400
							40	0123483	400
50.0	8.0 -0.6/+0.8	66.0 ± 1.2	16	64	275	1.88	20	0127277	400
							40	0124618	■
63.0	8.0 -0.6/+0.8	79.0 ± 1.5	16	64	300	2.40	20	0070691	200
							40	0123133	200
65.0	8.0 -0.6/+0.8	81.0 ± 1.5	16	64	310	2.45	20	0070692	200
							40	0070693	200
75.0	8.0 -0.6/+0.8	91.0 ± 1.5	16	64	350	2.89	20	0070694	200
							40	0125085	200
80.0	8.0 -0.6/+0.8	96.0 ± 1.5	16	64	375	3.02	20	0070695	200
							40	0070696	200
100.0	8.0 -0.6/+0.8	116.0 ± 1.5	16	64	450	3.60	20	0125916	200
							40	0123406	200

Branding



and embossed: TRELLEBORG - PUMPADUKT D - NBR1 - EN 1761 - EN 12115 - ND - D - PN 16 - Ω - month/year

